

PM43/PM43c/PM23c

Mid-Range Industrial Printers

The PM43 and even more compact PM43c mid-range industrial printers deliver fast print speeds, drop-in deployment, advanced connectivity and proven reliability. Built to deliver maximum uptime, PM Series printers are available with either a tamper-proof color touchscreen in 10 languages, or a universal icon interface. This enables immediate notifications through the printer interface, reducing your workforce training and device support needs.

As one of the most connected industrial printers on the market, the PM Series feature Wi-Fi and Cisco® CCX certifications, with additional Bluetooth® connectivity. Every printer ships with Ethernet connectivity, as well as network protocol IPv6, ensuring long-term enterprise scalability.

As a third-generation industrial printer platform, rugged PM Series printers incorporate features that increase uptime and reduce maintenance costs. A strong, metal construction is perfect for harsh industrial environments. And with Precision Print, even the smallest barcodes and images can be printed with pinpoint accuracy – no frequent media adjustments necessary.

Each PM43, PM43c and PM23c printer has an integrated web interface that allows for easy setup, monitoring and configuration through devices like handheld computers, tablets or smartphones. Integrated device management and diagnostic capabilities, provided through the Honeywell SmartSystems™ Foundation and Wavelink Avalanche®, reduce downtime and simplify deployment.

With fast print speeds up to 12 ips, you'll gain a clear productivity advantage. But performance isn't about just speed; it's also about working smarter. The PM Series printers are intelligent, helping you to reduce labeling errors and increase process efficiencies. In-printer apps, developed with Honeywell C# for Printers, can directly control



Considering the switch to Honeywell printers? With comprehensive command language support, including enhanced ZSim2 emulation, upgrading to the PM Series has never been simpler.

other devices such as scanners, scales, keyboards and other peripherals – without the need for an attached computer.

With their user-selectable, all-in-one programming languages, PM Series printers fit into most IT infrastructures, deploying quickly into existing Honeywell or mixed printer environments. And with comprehensive command language support – including ZSim2, our fast, friendly and complete ZPL-II emulation – upgrading to the PM Series has never been simpler.

The PM Series printers are co-engineered and tested with Honeywell Media Products, ensuring optimized printhead performance when used with genuine Honeywell media.

FEATURES & BENEFITS



Large color, multilingual, tamper-proof touchscreen or icon user interface.



Ready for the future, with IPv6 support, plus CCX and Wi-Fi certifications.



Comprehensive printer command language support, including ZSim2, makes upgrading easy.



Fast printing speed of up to 12 inches per second.



Run sophisticated apps right in the printer with industry-leading Honeywell Smart Printing supporting C#.

PM43/PM43c/PM23c Technical Specifications

DESCRIPTION

Industrial mid-range, direct thermal and thermal transfer label, ticket and tag printer. Also available with RFID.

PHYSICAL CHARACTERISTICS

PM43:

L x H x W: 483 mm x 295 mm x 284 mm
(19.0 in x 11.6 in x 11.2 in)

Weight: 15.82 kg (34.88 lb)

PM43c:

L x H x W: 431 mm x 181 mm x 253 mm
(17.0 in x 7.1 in x 9.9 in)

Weight: 12.5 kg (27.65 lb)

PM43c with Dome Door:

L x H x W: 500 mm x 245 mm x 253 mm
(19.6 in x 9.6 in x 9.9 in)

Weight: 12.71 kg (28.02 lb)

PM23c:

L x H x W: 431.84 mm x 181 mm x 205.5 mm
(17 in x 7.13 in x 8.09 in)

PM23c with Dome Door:

L x H x W: 500.22 mm x 244.87 mm x 205.5 mm
(19.69 in x 9.64 in x 8.09 in)

PM23c with Bag Tag Door:

L x H x W: 431.84 mm x 207 mm x 205.5 mm
(17 in x 8.15 in x 8.09 in)

Weight: 9.5 kg (21 lb)

PM43/43C PRINT SPECIFICATIONS

Max. Width at 203 dpi: 108 mm (4.25 in)

Max. Width at 300 dpi: 106 mm (4.17 in)

Max. Width at 406 dpi: 104 mm (4.09 in)

Max. Length at 203 dpi: 4.8 m (15.75 ft)

Max. Length at 406 dpi: 1.2 m (3.94 ft)

PM23C PRINT SPECIFICATIONS

Max. Width at 203 dpi: 56 mm (2.2 in)

Max. Width at 300 dpi: 56 mm (2.2 in)

Max. Width at 406 dpi: 64 mm (2.5 in)

RFID STANDARDS & FREQUENCIES

18000-6C / EPC Class 1 Generation 2

865-928 MHz radio configured to comply with local UHF RFID regulations including FCC and ETSI. Contact local representative for availability in particular regions.

PRINT SPEED

At 203/300 dpi: 100-300 mm/s (4-12 ips)

At 406 dpi: 100-250 mm/s (4-10 ips)

PRINT RESOLUTION

At 203 dpi: 8 dots/mm

At 300 dpi: 11.8 dots/mm

At 406 dpi: 16 dots/mm

MEDIA

Type: Labels and Tags, Linerless and Lined media

PM43/43c Max./Min. Width: 114/19 mm
(4.5/0.75 in)

Thickness: 3 mil to 10.4 mil

PM23c Max./Min. Width: 68/19 mm (2.7/0.75 in)

Configuration: Roll-fed or fanfold

Sensing: Gap, notch, black mark, continuous

Label Roll Max. Diameter: 152 mm (6 in) for long door models; 213 mm (8.38 in) for all other models

Label Roll Core: 38-76 mm (1.5-3 in)

Type: Ribbons

PM43 Roll Max. Diameter:

80 mm (3.15 in), approx. 450 m (1,476 ft)

PM23/43c Roll Max. Diameter:

61 mm (2.40 in), 229 m (751 ft)

Core ID: 25 mm (1 in)

Type: Wax, mid-range, resin

Genuine Honeywell Media:

www.honeywellaidc.com/media

INTERFACES

Standard:

Ethernet 10/100 Mbps

RS-232, up to 115.2 KB/s

Supported Serial Protocols:

Fingerprint/Direct Protocol: XON/XOFF, ENQ/ACK, DSR/DTR, RTS/CTS

IPL: XON/XOFF, Honeywell Std. Protocol

USB 2.0

USB Host (X1 on PM23c/PM43c, X2 on PM43)

Optional:

Parallel IEEE 1284

Industrial Interface (8 digital in/out, 4 analog relays, 1 RS-232/422/485 port)

Dual Serial ports RS-232, RS-422, RS-485 and 20 mA Current Loop

Dual USB Host

Wireless:

IEEE 802.11 a/b/g/n + Bluetooth

Wi-Fi Certified, CCX (Cisco) version 4 Certified

Static WEP (64-bit and 128-bit), Dynamic WEP (TLS, TTLS, PEAP, LEAP, EAP-FAST), WPA (TKIP/CKM Personal and Enterprise), WPA2 (AES-CCMP/CKM Personal and Enterprise)

Multiple industrial antenna options for maximized coverage

Supported Protocols:

TCP/IP suite (TCP, UDP, ICMP, IGMP), LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMPv1/2c/3, SNMP-MIBII supported – over UDP/IP (private enterprise MIB included), SMTP
Supports IPv4 and IPv6

PM43/PM43c/PM23c Technical Specifications

SOFTWARE

Printer Command Languages:

IPL, DP, ZSim2 (ZPL-II), DSim (DPL)
XML-enabled for SAP® All and Oracle® WMS

Applications/Drivers:

InterDriver Windows® printer driver
CUPS driver for Linux
Honeywell Device Types for SAP
Honeywell label design and print package

Smart Printing Languages:

Honeywell C# for Printers:

Smart Printing Developer Resource Kit
Write apps with .NET-compatible development environments

Honeywell Fingerprint:

Use Honeywell Fingerprint Application Builder

Configuration & Device Management Support:

PrintSet for printer configuration
SmartSystems for remote management
Sophisticated web interface for configuration, upgrade and 1:1 management
Wavelink Avalanche

BARCODE SYMBOLOGIES

All major 1D and 2D symbologies are supported.

STANDARDS SUPPORTED

UPC/EAN Shipping Container, UCC/EAN 128
Serial Shipping Container, MH10.8 Shipping Label,
AIAG (shipping parts label), OGMARS, POSTNET,
HIBCC, ISBT 128, GM1724, UPS Shipping label,
Global Transport Label

FONTS

Monotype font engine
Non-Latin fonts available through WTLE

GRAPHICS

Supports PCX, PNG, GIF and BMP file formats.
Other formats supported with Label
Generation Tools.

MEMORY

Standard: 128 MB Flash memory, 128 MB SDRAM,
Multi-GB USB memory device (FAT16/FAT32)

USER INTERFACE

Color Touch UI, Icon UI

USER INTERFACE LANGUAGES

On Color Touch LCD and Web Interface: English,
Russian, German, French, Portuguese, Spanish,
Italian, Korean, Simplified and Traditional Chinese

POWER SUPPLY

AC Voltage: 100 to 240V AC, 45 to 65 Hz

PFC Regulation: IEC320/C14

Power Consumption: Standby 9W; Peak 300W

OPERATING ENVIRONMENT

Ambient Operating Temperature:

+5°C to +40°C (+41°F to +104°F)

Storage Temperature:

-20°C to +70°C (-4°F to +152°F)

Humidity: 20 to 80% non-condensing

REGULATORY APPROVALS

RoHS Compliant, CE (EN55022 Class A),
FCC Class A, UL/cUL, D Mark and CCC

OPTIONS AND ACCESSORIES

Consult the PM Series Accessory Guide for full

details: Integral self-strip unit with liner takeup,
label taken sensor (LTS), media low sensor,
media supply hub, parallel interface board,
real-time clock, RFID UHF, additional serial
interface boards¹, industrial interface boards¹,
collapsible ribbon and liner core², cutter², linerless²,
full batch label/liner rewinder³

1 Not applicable when using IPL firmware.

2 Compatible with PM43 and PM43c only.

3 Compatible with PM43 only.

For a complete listing of all
compliance approvals and
certifications, please visit
[www.honeywellaidc.com/
compliance](http://www.honeywellaidc.com/compliance).

For a complete listing of
all supported barcode
symbologies, please visit
[www.honeywellaidc.com/
symbologies](http://www.honeywellaidc.com/symbologies).

Cisco is a trademark or
registered trademark of
Cisco Systems, Inc. in
the United States and/
or other countries.

Bluetooth is a trademark
or registered trademark
of Bluetooth SIG in
the United States and/
or other countries.

SmartSystems is a
trademark or registered
trademark of Honeywell
International Inc. in
the United States and/
or other countries.

Wavelength Avalanche
is a trademark or
registered trademark of
Wavelength Corporation
in the United States and/
or other countries.

SAP is a trademark or
registered trademark
of SAP SE in the
United States and/
or other countries.

Oracle is a trademark
or registered trademark
of Oracle Corporation in
the United States and/
or other countries.

Windows is a trademark
or registered trademark
of Microsoft Corporation
in the United States and/
or other countries.

For more information

www.honeywellaidc.com

Honeywell Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707
800-582-4263
www.honeywell.com

PM43/43c/23c Data Sheet | Rev G | 03/17
© 2017 Honeywell International Inc.

Honeywell
THE POWER OF **CONNECTED**