




# COUNTER SCALES WIND SERIES (500 RANGE)

Price computing counter scales, with receipt or label printer and PC connection. High performance and easy to use scales.




# INFORMATION



The Wind Series retail scales are the most basic ones in their range. They are easy to use scales designed for the counter with extensive features due to their memory, their fast and reliable communications among scales, PC and mobile devices. Two formats, different displays and receipt or label printers are available.

Manage your business easily with Dibal Wind Series retail scales.



## Data in mm

<b>A</b>	365
<b>B</b>	440

---

<b>C</b>	160
----------	-----

<b>D</b>	530
----------	-----

---

Plate dimensions: L360 x W260 mm

## MAIN CHARACTERISTICS

- **Electronic scale with higher visibility display options.**
- **Models with receipt printer or label printer (suitable for receipts).**
- **Functional and robust design.**
- **Compliance with EU Regulation 1169/2011 on the provision of food information to consumers (only for W-025).**

## FEATURES

- **Extensive information for each PLU: normal price, price for weight scales and by kg/100 g (in W-020, W-020 B and W-025), 2 names of 20 characters (1 in W-010, W-010 B and W-015), 10 free texts of 24 characters (5 in W-010, W-010 B and W-015), 1 text of 3,000 characters (in W-025), profitability codes, etc.**
- **PLU search by code or name.**
- **Preset keys to programming menus: to change prices, register PLUs or vendors, etc.**
- **Direct access to 999 PLUs from the keyboard.**
- **Drill down menu.**
- **Printing of scale menus.**
- **2 programmable macros (in W-020, W-020 B and W-025): recording of a sequence of keys to create direct access to any task (reopening of receipts, lists, change in batcher number, etc.).**
- **Sales and management reports: sales (by article, vendor, time frames, last month, etc.), balance available in the cash drawer, modified PLUs, etc.**
- **Fast and reliable communication between scales, with PC and mobile devices (via DWS).**
- **Stocks management on the scale.**
- **Option to record normal price for each article.**
- **Stock / order mode.**

## CAPACITY / ACCURACY

- **Multirange (3,000 divisions): 6 kg / 2 g - 15 kg / 5 g.**
- **Optional:**
  - Monorange (3,000 divisions): 15 kg / 5 g or 30 kg / 10 g.
  - Multirange (3,000 divisions): 15 kg / 5 g - 30 kg / 10 g.
  - Monorange (6,000 divisions): 12 kg / 2 g or 30 kg / 5 g.

## FORMATS

- **Flat.**

- Pole.

## CONSTRUCTION

- Highly resistant ABS plastic casing.
- Stainless steel plate.

## DISPLAYS

- Backlit LCD segment display (W150.2 x H43.4 mm) for vendor and buyer (showing weight, price / kg, total, tare, vendor and name of articles).
- Optional:
  - LCD matrix graphic display (W134 x H41 mm) for vendor and buyer, for W-020, W-020 B and W-025. Possibility of showing: logos, profitability codes, warning messages sent from a PC (on vendor display) and advertising messages with animated effects on buyer display.

## PRINTER

- Models available with 1 printer for receipts or 1 printer for labels (also suitable for receipts by changing the paper roll and the working mode).
- 54 mm thermal printer.
- High resolution (8 dots/mm).
- Speed depending on models:
  - W-020 and W-025: 100 mm/sec.
  - W-010 and W-015: 80 mm/sec.
  - W-010 B and W-020 B: 60 mm/sec.

## RECEIPTS

- All the models:
  - 15 fonts (6 monospaced + 9 multispaced: more modern and legible).
  - Up to 40 items.
  - EAN-13 barcode.
  - 9 payment methods.
  - Total in National currency and other 3 different currencies.
  - Discounts per line and total.
- W-010, W-010 B and W-015 models:
  - 2 fixed formats.
- W-020, W-020 B and W-025 models:
  - 2 fixed formats + 1 programmable format.
  - 4 logos per receipt.
  - Name of vendor.
  - Customers on account.

## LABELS

- All the models:

- 15 fonts (6 monospaced + 9 multispaced: more modern and legible).
- 40 logos.
- EAN-13 barcode.
- 40 fields of information.
- 100 programmable texts.
- Manual and automatic pre-packaging modes.
- Automatic adjustment of the paper detection option.
- **W-015 models:**
  - From W30 x L30 mm to W60 x L80 mm.
  - 20 fixed formats + 5 programmable formats.
  - 1 type of generic traceability (for meat, fish, fruits, vegetables, etc.) up to 10 products. Included in the prevailing European legislation on bovine traceability.
- **W-025 models:**
  - From W30 x L30 mm to W60 x L100 mm.
  - 20 fixed formats + 10 programmable formats.
  - 3 levels of totals.
  - Printing of “n” identical labels.
  - Printing with 90°, 180° and 270° rotation.
  - Packaging date, expiry date and extra date (for any application).
  - Alphanumeric batch number.
  - 2 types of generic traceability (for meat, fish, fruits, vegetables, etc.) up to 20 products. Included in prevailing European legislation on bovine traceability.

## FOOD INFORMATION

- **W-010, W-010 B and W-015 models:**
  - Minimum letter size: 1.2 mm.
  - For direct sale receipts and labels: possibility of indicating in the PLU name (with an \* or other symbol) those that contain allergens and programming a text, such as “\* Consult allergens.
  - Labels do not comply with the labelling of packaged food Regulation (only 5 texts of 24 characters are available).
- **W-020, W-020 B and W-025 models:**
  - Minimum letter size: 1.2 mm.
  - Effect (bold, underlined, or both) for each character in the text.
  - Possibility of using the general text “G” (2,048 characters) for ingredients, in lower case or UPPER CASE to highlight allergens.
  - Possibility of including a table of nutritional facts.
  - Free texts (10 x 24 characters).
  - For direct sale receipts and labels: possibility of indicating in the PLU name (with an \* or other symbol) those that contain allergens and programming a text, such as “\* Consult allergens”.
  - Possibility of printing 2 labels for each operation: programmable by PLU, configurable information, 2nd automatic or manual label (also to be used as promotional labels).
  - **W-025 model complies with EU Regulation 1169/2011 on the provision of food**

information to consumers as of 13 December 2016.

## COMMUNICATIONS

- **TCP/IP Ethernet for interconnection and connection to PC.**
- **RS-232, for connection to scanner (in W-020, W-020 B and W-025).**
- **Optional:**
  - Wi-Fi.

## SECURITY

- **Access to different protected programming menus via configurable passwords.**

## INTERCONNECTION

- **W-010, W-010 B and W-015 models:** up to 5 scales per section.
- **W-020, W-020 B and W-025 models:** up to 10 scales per section.

## CONNECTIVITY WITH OTHER DEVICES

- **PC.**
- **Bar code scanner** (powered by the scale – 5 VDC) to read EAN-13 bar codes (in W-020, W-020 B and W-025).
- **Cash drawer.**

## SOFTWARE (SEE SECTION ON SOFTWARE)

### PC software:

- **DFS:**
  - Programming of scales.
  - Receipt of sales data.
  - Data backup copy.
  - Graphic design of receipts and labels.
  - Design and management of advertising images for graphic display.
- **RMS\*:**
  - Programming and management of scales.
  - \* Does not manage:
    - Images (of articles and advertising).
    - Specific functions of Wind scales.
- **DLD:**
  - Graphic design of receipts and labels.
- **Integration tools: in Windows or Linux to facilitate communication with the Back-Office.**

### Scale firmware:

- **DWS (Dibal Web Server):**
  - Allows access to the information on each scale (via passwords) from any computer or

mobile device with an Internet browser.

## POWER SUPPLY

- **Mains: 110 up to 230 VDC.**
- **Depending on the models, also:**
  - High performance rechargeable internal battery (W-010 B and W-020 B): up to 36 hours of life (calculated for 1,000 receipts, with 3 articles per receipt) and connector to external battery 12 V.
  - Anti-blackout rechargeable internal battery 24 V and connector to external battery 24 V.

## MODELS

---

---

### W-010 F

**Ref.:** 7W101PBLGE\_\_

**Flat format**

- **Displays:** LCD Segment.
- **Printer:** Receipts.
- **PLUs:** 2,000.
- **Direct PLUs :** 45x2 + 4x2\*.
- **Vendors:** 5.
- **Power:** Mains.
- **Capacity / Accuracy:** 6 kg / 2 g - 15 kg / 5 g.

\*Using the Shift key and those of Vendor.

---

### W-010 B F

**Ref.:** 7W111PBLGE\_\_

**Flat format with internal battery**

- **Displays:** LCD segment.
- **Printer:** Receipts.
- **PLUs:** 2,000.
- **Direct PLUs :** 45x2 + 4x2\*.
- **Vendors:** 5.
- **Power:** Mains / Battery.
- **Capacity / Accuracy:** 6 kg / 2 g - 15 kg / 5 g.

\* Using the Shift key and those of Vendor.

---

## W-020 F

Ref.: 7W201PBLGE\_\_

### Flat format

- **Displays:** LCD segment.
- **Printer:** Receipts.
- **PLUs:** 5,000.
- **Direct PLUs :** 40x2 + 9x2\*.
- **Vendors:** 10.
- **Power:** Mains.
- **Capacity / Accuracy:** 6 kg / 2 g - 15 kg / 5 g.

\* Using the Shift key and those of Vendor.

---

## W-020 B F

Ref.: 7W211PBLGE\_\_

### Flat format with internal battery

- **Displays:** LCD segment.
- **Printer:** Receipts.
- **PLUs:** 5,000.
- **Direct PLUs :** 40x2 + 9x2\*.
- **Vendors:** 10.
- **Power:** Mains / Battery.
- **Capacity / Accuracy:** 6 kg / 2 g - 15 kg / 5 g.

\* Using the Shift key and those of Vendor.

---

## W-010 P

Ref.: 7W101TBLGE\_\_

### Pole format

- **Displays:** LCD segment.
- **Printer:** Receipts.
- **PLUs:** 2,000.
- **Direct PLUs :** 45x2 + 4x2\*.
- **Vendors:** 5.
- **Power:** Mains.
- **Capacity / Accuracy:** 6 kg / 2 g - 15 kg / 5 g.



\* Using the Shift key and those of Vendor.

---

## W-010 B P

Ref.: 7W111TBLGE\_\_

### Pole format with internal battery

- **Displays:** LCD segment.
- **Printer:** Receipts.
- **PLUs:** 2,000.
- **Direct PLUs :** 45x2 + 4x2\*.
- **Vendors:** 5.
- **Power:** Mains / Battery.
- **Capacity / Accuracy:** 6 kg / 2 g - 15 kg / 5 g.

\* Using the Shift key and those of Vendor.

---

## W-020 P

Ref.: 7W201TBLGE\_\_

### Pole format

- **Displays:** LCD segment.
- **Printer:** Receipts.
- **PLUs:** 5,000.
- **Direct PLUs :** 40x2 + 9x2\*.
- **Vendors:** 10.
- **Power:** Mains.
- **Capacity / Accuracy:** 6 kg / 2 g - 15 kg / 5 g.

\* Using the Shift key and those of Vendor.

---

## W-020 B P

Ref.: 7W211TBLGE\_\_

### Pole format with internal battery

- **Displays:** LCD segment.
- **Printer:** Receipts.
- **PLUs:** 5,000.
- **Direct PLUs :** 40x2 + 9x2\*.
- **Vendors:** 10.
- **Power:** Mains / Battery.
- **Capacity / Accuracy:** 6 kg / 2 g - 15 kg / 5 g.

\* Using the Shift key and those of Vendor.

---

## W-015 F

Ref.: 7W151PBLGE\_\_

### Flat format

- **Displays:** LCD segment.
- **Printer:** Labels (or Receipts).
- **PLUs:** 2,000.
- **Direct PLUs :** 45x2 + 4x2\*.
- **Vendors:** 5.
- **Power:** Mains.
- **Capacity / Accuracy:** 6 kg / 2 g - 15 kg / 5 g.

\*Using the Shift key and those of Vendor.

---

## W-025 F

Ref.: 7W251PBLGE\_\_

### Flat format

- **Displays:** LCD segment.
- **Printer:** Labels (or Receipts).
- **PLUs:** 5,000.
- **Direct PLUs :** 40x2 + 9x2\*.
- **Vendors:** 10.
- **Power:** Mains.
- **Capacity / Accuracy:** 6 kg / 2 g - 15 kg / 5 g.

\*Using the Shift key and those of Vendor.

---

## W-015 P

Ref.: 7W151TBLGE\_\_

### Pole format

- **Displays:** LCD segment.
- **Printer:** Labels (or Receipts).
- **PLUs:** 2,000.
- **Direct PLUs :** 45x2 + 4x2\*.
- **Vendors:** 5.
- **Power:** Mains.
- **Capacity / Accuracy:** 6 kg / 2 g - 15 kg / 5 g.

\*Using the Shift key and those of Vendor.

## W-025 P

Ref.: 7W251TBLGE\_ \_

### Pole format

- **Displays:** LCD segment.
- **Printer:** Labels (or Receipts).
- **PLUs:** 5,000.
- **Direct PLUs :** 40x2 + 9x2\*.
- **Vendors:** 10.
- **Power:** Mains.
- **Capacity / Accuracy:** 6 kg / 2 g - 15 kg / 5 g.

\*Using the Shift key and those of Vendor.

## OPTIONS



OPTION	CHARACTERISTICS	REF.
<b>Capacity 15 kg / 5 g - 30 kg / 10 g</b>	Multirange (3,000 divisions).	...F_ _ (*)
<b>Capacity 15 kg / 5 g</b>	Monorange (3,000 divisions).	...N_ _ (*)
<b>Capacity 30 kg / 10 g</b>	Monorange (3,000 divisions).	...Y_ _ (*)
<b>Capacity 12 kg / 2 g</b>	Monorange (6,000 divisions).	...V_ _ (*)
<b>Capacity 30 kg / 5 g</b>	Monorange (6,000 divisions).	...P_ _ (*)
<b>Graphic display (W134 x H41 mm)</b>	LCD matrix graphic display for buyer and vendor.	Contact us
<b>Wi-Fi</b>	Wireless communications (IEEE 802.11n).	Contact us

OPTION	CHARACTERISTICS	REF.
<b>Anti-blackout</b>	Anti-blackout internal battery 24 V + external battery connector 24 V.	Contact us
<b>DFS Software</b>	Scale configuration, receipt of sales data for processing with other IT applications, data backup (LBS), and labels and receipts graphic design. (See section on software).	7340F1U1 / 7340FNU1 / 7340D1U1 / 7340DNU1
<b>RMS Software</b>	Scale configuration, receipt of sales data for processing with other IT applications and data backup (LBS). (See section on software).	73400000 / 7340R1U1 / 7340RNU1
<b>DLD Software</b>	Labels and receipts graphic design. (See section on software).	7340LOU1 / 7340L1U1 / 7340LNU1
<b>Technical DWS</b>	Dibal Web Server software for the remote configuration of the scale. (See section on software).	7340W101
<b>Full DWS</b>	Dibal Web Server software for the remote configuration of the scale and the processing of the information generated. (See section on software).	7340WN01
<b>Metrological verification (M)</b>	According to EU weighing directives. (See section on equipment metrological verification).	Contact us

(\*)

The scale references with this capacity are obtained by replacing the last characters of the reference for the standard scale with the indicated ending.

## ACCESSORIES



### **SMALL ITALIAN PLATE**

L357 x W235 x H55 mm.



### **LARGE ITALIAN PLATE**

L407 x W284 x H60 mm.



### **INTERCONNECTION SWITCH**

For scales with rechargeable internal battery (W-010 B and W-020 B).



### **BATTERY FOR THE SWITCH**

Power battery for the BHN99 interconnection switch.



### **BAR CODE SCANNER**

Includes connection cable to the scale (for W-020, W-020 B and W-025).



Astintze, 26  
48160 Derio (Vizcaya) Spain  
**T.** (+34) 94 452 15 10  
**E.** [dibal@dibal.com](mailto:dibal@dibal.com)